

eMetal 0.8m – for Buildings & BIPV




Description

The eMetal is a semi-flexible and lightweight solar panel designed for installation on roof structures with limited load bearing capacity, aesthetical metal BIPV facades and many more demanding solar applications.

Features

- Most elegant and aesthetic solar module, beautiful uniform design
- High energy yield due to excellent shadow tolerance and temperature stability
- Easy installation – drill & fix –mounting instruction available on request
- Applicable for roofs and facades – semi-bendable
- Ultra-low weight, < 4 kg/m²
- Unbreakable & robust - no glass, no micro cracks
- EL tested
- Made in Switzerland
- Available in 0.8m, 1.6m, 2.3m and 3m length
- Available with black frame color for highest aesthetics



Dimensions			
Length	[mm]		831
Width	[mm]		448
Thickness at module	[mm]		2.2
Thickness at J-Box	[mm]		21 ± 1
Weight	[Kg]		1.6

Electrical characteristics at STC ¹				SF 25	SF 30
Model number					
Nominal power	Pmpp	[W]		25	30
Tolerance		[W]		-0/+5	-0/+5
Voltage at nom. power	Vmpp	[V]		34	34
Current at nom. power	Impp	[A]		0.74	0.88
Open circuit voltage	Voc	[V]		46	46
Short circuit current	Isc	[A]		0.82	0.97
Max. system voltage	IEC	[V]			1000
Max. serial fuse rating		[A]			10

Thermal characteristics			
Temperature coefficient	Voc	[%/°C]	-0.3
Temperature coefficient	Isc	[%/°C]	0.01
Temperature coefficient	Pmpp	[%/°C]	-0.35

Operating conditions			
Temperature range	[°C]		-40 to +85
Max. mechanical load			2400 Pa, 245 kg/m ²

Additional data	
Cell type	Flexible CIGS
Junction box	Front side including bypass diode, IP67, MC4 type / MC4 connectors, 700mm long cable (4mm ²)
Encapsulation	Fluoropolymer front sheet / 1mm alu back plate
Parallel connection	Y-connector available
Customization	Possible on request for larger volumes / Optional front and back-side junction box

Warranty & certification	
Performance guarantee	10 years on 90% of Pmpp under STC ¹ & 20 year on 80% of Pmpp under STC ¹
Warranty	5 years' workmanship after delivery date
Certification	IEC 61646 2nd Ed; IEC 61730
Safety class	II

Notes

¹ STC: 1000 W/m², AM1.5G, 25°C, stabilized module state

² NOCT: 800 W/m², AM1.5G, 20°C, Wind Velocity = 1 m/s

We continuously develop our products. Electrical and physical properties subject to change without prior notice.

Distribution & Installation Partner: